BTMARK

BTMARK

Since 2003

TIJ

Online Inkjet Printer

- ➤ **Maximum printing height up to 150mm**
- ➤ **Multi-color printing at the same time**
- ➤ **Variable data real-time printing**

16:04:42
2021年03月16日 星期二

打印   文件   编辑   设置

Intelligence marking system provider

TIJ Inkjet Online Printer

▶ Intelligent Operating

1. Linux Operating System
2. Import database from USB flash drive
3. Variable data real-time printing

▶ Flexible Combination

1. Support 6 sprinkler combinations
2. Realize simultaneous printing
3. Meet the customization requirements of different products

▶ Convenient Installation

1. Separate fuselage design for easy installation
2. It comes with a 360° print kit
3. The printing Angle can be adjusted arbitrarily

▶ Stable Operation

1. Streamlined all-aluminum body
2. Good heat dissipation suitable for long time printing

Application Area:

Widely used in plastic packaging, food packaging, beverage packaging, electronic film, plastic, textile,pharmaceutical coding, daily chemical spray code, glasses, printing and other industries. Suitable for marking, carving, hollowing and cutting all kinds of non-metallic materials and products. It can mark, engrave, hollow out and cut all kinds of characters, symbols, graphics, images, bar codes, serial numbers, etc.

TIJ Online Inkjet Printer

HD Printer Specification			
Name	H−D Printer	The System	Linux 3.4
Size	210*110*40mm	Material	Aluminum
Nozzle	TIJ Hot foaming nozzle	Information is stored	3GB
Screen Size	7 Inch capacitive screen	Spray printing precision	600 DPI
Count number	1−15 digits	Nature of the Ink	Dry,Wet,Oil
Spray printing speed	50m/min	The cartridge capacity	42ml
Print library	Synchronous machine library	Print distance	3−5mm
Water−based ink color	Black,Red,Blue,Green,Yellow,Invisible Color		
Quick drying ink color	Black,Red,Blue,Green,Yellow,White,Invisible Color		
The external interface	Power,HOMI cable interface,USB interface		
Using the environment	Temperature 0 to 40,10−80% humidity		
Printing Height	Max 150mm(Any 1−6 head splice)		
Adapter parameters	100−240V AC input		
Spray print type	TXT,Bar−code,logo,QR code		
Printing material	Plate,carton,pipe,cable,metal, plastic, etc		
Manipulation Language	Chinese,English,Russian,French,Spanish,Arabic,etc		
Bar Code Type	Code 128,Code 39,Int25,UPCA,ENA 13,QR Code,Data Matrix		